

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number  
**WO 2005/085685 A1**

(51) International Patent Classification<sup>7</sup>: **F16J 15/08**

(21) International Application Number:  
PCT/US2005/006469

(22) International Filing Date: 28 February 2005 (28.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/521,154 28 February 2004 (28.02.2004) US

(71) Applicant (for all designated States except US):  
**SWAGELOK COMPANY** [US/US]; 29500 Solon  
Road, Solon, OH 44139 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BENNETT, Mark,  
A.** [US/US]; 18436 Snyder Road, Bainbridge Township,


OH 44023 (US). **CARLSON, George, A.** [US/US]; 1259  
Sandy Lake Road, Ravenna, OH 44266 (US). **GAUSMAN,  
Theodore, J.** [US/US]; 11516 Girdled Road, Concord, OH  
44077 (US). **JAGIELO, Joseph, J.** [US/US]; 1165 Dorsh  
Road, South Euclid, OH 44121 (US). **MARUNA, Tim-  
othy, J.** [US/US]; 10773 Claridon Troy Road, Chardon,  
OH 44024 (US). **NORDSTROM, Douglas, A.** [US/US];  
18707 Lomond Blvd., Shaker Heights, OH 44122 (US).  
**WILLIAMS, Peter, C.** [US/US]; 3495 Edison Road,  
Cleveland Heights, OH 44121 (US).

(74) Agent: **SZABO, Paul, E.**; Calfee, Halter & Griswold LLP,  
800 Superior Avenue, Suite 1400, Cleveland, Ohio 44114  
(US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

[Continued on next page]

(54) Title: SEAL ASSEMBLY FOR FLUID COMPONENTS



(57) Abstract: A seal (10) includes a seal structure (130) for engagement with first (24) and second fluid components (26) in first (84) and second counterbores (88). The seal also includes a holding plate (20, 30) structure for engagement with first (81) and second surfaces (85) of the components. The holding plate structure includes one or more layers that are preferably formed with the outer layers of the seal structure (30). The seal structure preferably includes at least three abutting layers of metal, the inner layer (70) having a hardness that is selected to be greater than the hardness of the first and second outer layers (20, 30). The invention also relates to a method of achieving a metal to metal seal between two relatively hard metal components in a fluid system.



KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

**(84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*